



Web-based RFID & PIN Controller

SI-FP-05

FEATURES

- Log data real time PUSH
- RFID card + password verification
- Standalone with build in webserver
- Simplified installation with cat-6 cable
- Assign IP camera for capturing snapshot
- Proximity (EM/ Mifare/ Desfire/ Mobile NFC & BLE)
- Network optix video management system version available
- Weatherproof IP65 rate suitable for both indoor and outdoor environment



SPECIFICATION

- | | |
|-------------------------------|--|
| • Model Available | : SI-FP-05 (Web-based RFID & PIN Controller) |
| • Verification Mode | : Card/ PIN/ Card+PIN |
| • Software Application | : Software/ Browser |
| • Proximity | : EM/ Mifare/ Desfire/ Mobile NFC & BLE |
| • Card Capacity | : 20,000 (50,000 extendable) |
| • System Log | : 1,536 |
| • Entry Log | : 65,535 |
| • Time Set/ Time Zone/ Group | : 255/ 120/ 255 Sets |
| • Holiday/ Event Handle | : Yes/ Yes |
| • Anti Pass Back/ Anti Duress | : Yes/ Yes |
| • Touch Keypad | : Yes |
| • LED Indicators | : Blue/ Green/ Red LED |
| • Inputs | : 3 inputs, Exit button/ Door sensor/ Fire alarm |
| • Communications | : TCP/IP, Wiegand input/ RS485 |
| • Power Requirement | : 9~24VDC/1A |
| • Power Consumption | : 560mA ± 5% |
| • Operating Temperature | : 0°C ~ 55°C |
| • Operating Humidity | : 5%~80% RH |
| • Dimension | : 78.5 x 129 x 23 mm |

* Design & dimension subject to change without prior notice, please contact us for further information.



SECURIKO

MORE THAN JUST ACCESS