

Fingerprint Access Control

SI-FP-03

FEATURES

- LOGs data real time PUSH
- Anti pass-back/ Anti duress
- TCP/IP standalone biometrics controller
- Support AUTO Get IP (DHCP) for easy setup
- Basic Time & Attendance (First IN/ Last OUT)

SPECIFICATION

- Model Available : SI-FP-03 (Fingerprint Access Control)
- Verification Mode : Fingerprint/ Card
- Software Application : Software/ Browser
- Proximity : EM/ Mifare/ Desfire/ HID
- Template Capacity : 9,590
- Card Capacity : 20,000
- System Log : 1,536 entries
- Entry Log : 51,968 entries
- Time Set/ Time Zone/ Group : 255/ 120/ 255 Sets
- Holiday/ Event Handle : Yes/ Yes
- Anti Pass Back : Yes
- Communications : TCP/IP, Wiegand input/ RS485
- Inbuilt Relays : Door Lock
(Max. power loading) (40VAC/ 40VDC,2A)
- Power Requirement : 9~24VDC/1A
- Power Consumption : 500mA \pm 5%
- Operating Temperature : 0°C ~ 65°C
- Operating Humidity : 5%~80% RH
- Dimension : 160 x 56.9 x 40.1 mm

* Design & dimension subject to change without prior notice,
please contact us for further information.

