

# MEDIATOR® lock, tubular frame version



## Product description

The MEDIATOR® lock in its tubular frame version is available with different backsets and a comprehensive range of accessories.

## Overview of Advantages

- Automatic locking system: Bolt and latch are blocked, therefore higher level of security
- Mechanical follow up control between double action latch and control latch
- Integrated panic function via internal door handle
- Changeover function for unlocking with a key from the outside
- Minimum rear backset for tubular frame design: 15 mm

## Note

- MEDIATOR® locks have a bolt through the handle and thus require front door furniture (inside handle or panic push bar, outside knob or push bar).

## Technical data

Backset	30, 35, 40, 45 mm
Distance	Euro profile cylinder: 92 mm
Type of cylinder	Euro profile cylinder
Bolt throw	20 mm
Handle follower	9 mm
VdS-approval	G 109 032, M 109314, Z 109001
Approval DIN EN 179	Certificate of Constancy of performance 0432-CPR-00007-11
DIN EN 1125 approval	Certificate of Constancy of performance 0432-CPR-00007-12
Building authorities test certificate	P-120003555
Mech. strength (EN 12209:2004)	200,000 cycles, 50N load on latch, Class 6 protection

## Variants that can be ordered

Order number	Description
609-102PZ-----1	Tubular frame; backset 30 mm; distance 92 mm; spindle 8-9 mm; angular face plate 24 mm
609-202PZ-----1	Tubular frame; backset 35 mm; distance 92 mm; spindle 8-9 mm; angular face plate 24 mm
609-302PZ-----1	Tubular frame; backset 40 mm; distance 92 mm; spindle 8-9 mm; angular face plate 24 mm
609-402PZ-----1	Tubular frame; backset 45 mm; distance 92 mm; spindle 8-9 mm; angular face plate 24 mm

