

MEDIATOR® lock, wooden and steel door version

Product description

The MEDIATOR® lock in its full leaf version is available with different backsets and a comprehensive range of accessories.

Overview of Advantages

- Automatic locking system: Bolt and latch are blocked, therefore higher level of security
- Mechanical follow up control between double action latch and control latch
- Integrated panic function via internal door handle
- Changeover function for unlocking with a key from the outside

Note

- MEDIATOR® locks have a bolt through the handle and thus require front door furniture (inside handle or panic push bar, outside knob or push bar).

Technical data

Backset	55, 60, 65, 80, 100 mm
Distance	Euro profile cylinder: 72 mm
Width face plate	20 mm
Bolt throw	20 mm
Handle follower	9 mm
Approval DIN EN 179	Certificate of Constancy of performance 0432-CPR-00007-11
DIN EN 1125 approval	Certificate of Constancy of performance 0432-CPR-00007-12
VdS-approval	G 109 032, M 109314, Z 109001, P-120003555
Building authorities test certificate	P-120003555
Mech. strength (EN 12209:2004)	200,000 cycles, 50N load on latch, Class 6 protection

Variants that can be ordered

Order number	Description
609-501PZ-----1	Full leaf; backset 55 mm; distance 72 mm; spindle, 8-9 mm; face plate, 20 mm, round
609-502PZ-----1	Full leaf; backset 55 mm; distance 72 mm; spindle 8-9 mm; round face plate 24 mm
609-601PZ-----1	Full leaf; backset 60 mm; distance 72 mm; spindle, 8-9 mm; face plate, 20 mm, round
609-602PZ-----1	Full leaf; backset 60 mm; distance 72 mm; spindle 8-9 mm; round face plate 24 mm
609-701PZ-----1	Full leaf; backset 65 mm; distance 72 mm; spindle, 8-9 mm; face plate, 20 mm, round
609-702PZ-----1	Full leaf; backset 65 mm; distance 72 mm; spindle 8-9 mm; round face plate 24 mm
609-70RPZ-----1	Full leaf; backset: 65 mm; centre distance: 72 mm; spindle, 8-9 mm; Renovation Front plate 24 x 280 mm
609-801PZ-----1	Full leaf; backset 80 mm; distance 72 mm; spindle, 8-9 mm; face plate, 20 mm, round
609-802PZ-----1	Full leaf; backset 80 mm; distance 72 mm; spindle 8-9 mm; round face plate 24 mm
609-901PZ-----1	Full leaf; backset 100 mm; distance 72 mm; spindle, 8-9 mm; face plate, 20 mm, round
609-902PZ-----1	Full leaf; backset 100 mm; distance 72 mm; spindle 8-9 mm; round face plate 24 mm

